

*The Aspirated Radiation Shield provides maximum sensor protection from incoming short wave solar radiation and outgoing long wave radiation.*

The shield employs a triple walled intake tube and multiple canopy shades to isolate the sensor from precipitation and solar radiation. A continuous duty blower draws ambient air through the intake tubes and across the sensor minimizing radiation errors. Compact shield components reduce radiation-absorption and improve aspiration efficiency. Specially selected plastic materials provide high reflectivity, low conductivity, and maximum weatherability.

The versatile DC blower is designed for continuous duty of more than 80,000 hours (9 years) at 25° C (77°F). Brushless electronic commutation is achieved using dependable solid state circuitry.

The Temperature Probe is a precision Platinum RTD encased in a stainless steel protective sheath. The sensing element is secured in a convenient junction box that fits YOUNG radiation shields. The probe is available with various output options. The 4-20 mA current output is useful in high noise, industrial settings or for long cable lengths. The 0-1 VDC option provides a calibrated voltage output signal.

The Relative Humidity/Temperature Probe combines a high accuracy humidity sensor and temperature sensor into one compact unit. The probe is available with 0-1 VDC or 4-20 mA outputs to satisfy a wide variety of applications.



## Specifications

**Sensor Types:**  
Accommodates temperature and humidity sensors up to 24 mm (.94 in) diameter

**Radiation Error:**  
@ 1000 W/m<sup>2</sup> intensity  
Ambient Temperature: 0.2° C (0.4° F) RMS  
Delta T: 0.05° C (0.1° F) RMS with like shields equally exposed.

**Aspiration Rate:**  
6.8 to 9.2 m/s (22 to 30 fps) depending on sensor size.

**Construction:**  
UV stabilized white thermoplastic shield and blower housing  
Aluminum mounting bracket, white coated.  
Stainless Steel U-bolt clamp

**Dimensions:**  
Overall Height: 32 cm (12.6 in).  
Overall Diameter: 20 cm (8 in).  
Shield: 60 mm (2.4 in) dia. x 12 cm (4.7 in) length.  
Blower Housing: 17 cm (6.7 in) dia. x 11 cm (4.3 in) length.  
Mounting: V-block and U-bolt fits vertical post or tower members 25-50 mm (1-2 in) dia.

**Power Requirement:**  
12 VDC @ 500 mA for blower.  
AC adapter included.

**Weight:**  
Net weight- 1.1 kg (2.5 lb)  
Shipping weight- 2.7 kg (6 lb)

**\*SPECIFY TEMPERATURE SCALING:**  
-50 to +50° C ..... ADD SUFFIX C  
-50 to +150° F ..... ADD SUFFIX F

## Ordering Information

## MODEL

ASPIRATED RADIATION SHIELD .....	43502
TEMPERATURE PROBE- RTD OUTPUT .....	41342
4-20 MA OUTPUT* .....	41342L *
0-1 VDC OUTPUT* .....	41342V*
RELATIVE HUMIDITY/TEMPERATURE PROBE*	
4-20 MA OUTPUT* .....	41382L *
0-1 VDC OUTPUT* .....	41382V*



Complies with applicable CE Directives



**R.M. YOUNG COMPANY**  
2801 Aero Park Drive  
Traverse City, Michigan 49686 USA  
TEL: (231) 946-3980 FAX: (231) 946-4772  
E-mail: met.sales@youngusa.com  
Web Site: www.youngusa.com