

*Temperature & Humidity  
Display With Alarms*



Model 46203  
**Temp Tracker**

*The Temp Tracker is a versatile temperature and relative humidity indicator.*

Measured values are displayed on the front panel in large illuminated digits: temperature is shown on the left, relative humidity or dewpoint is shown on the right. Maximum and minimum values are saved and can be viewed at any time.

The Temp Tracker includes the following useful features: fully-programmable alarms for both channels, calibrated voltage outputs for connection to recording devices, and RS-485 output for interfacing with serial devices. A front panel brightness control is also included.

Input for the Temp Tracker is supplied by **Model 41372LC Relative Humidity/ Temperature Probe** which provides a convenient 4-20 mA current loop signal for each channel. For best accuracy, the probe should be housed in a protective shield. **Model 41002P Multi-Plate Radiation Shield** combines excellent performance and moderate cost.



The Temp Tracker is supplied with an adjustable bracket for wall or bench mounting. With the bracket removed, the housing is sized to fit standard

DIN panel configurations. The low profile design is easily installed on bulkheads or wall surfaces. DC power allows the Temp Tracker to be powered by external batteries or AC wall adapter (included).



## Specifications

### Range:

Temperature: -50.0 to 150.0°F, -50.0 to 50.0°C  
Relative Humidity: 0 to 100%

### Display Resolution:

Temperature: 0.1°C, 0.1°F  
Relative Humidity: 1%  
Dewpoint: 1°C, 1°F

### Compatible Sensors:

Model 41372LC (T & RH)  
Model 41342LC (T only)

### Voltage Outputs:

0-5 VDC Full Scale for T & RH

### Alarm Relays:

Normally open contacts for T & RH  
Contact rating 5A resistive,  
2A inductive @ 250 VAC, 30 VDC

### Remote Displays:

16 maximum

### Power Requirement:

12 to 30 VDC, 4.5 W

### Dimensions:

144 mm (5.65 in) x 144 mm (5.65 in) x 36 mm (1.4 in)

### Panel Cutout:

138 mm (5.43 in) x 138 mm (5.43 in)

### Weight:

1 lb (0.45 kg)

### Shipping Weight:

3 lb (1.4 kg)

## Ordering Information

## MODEL

TEMP TRACKER- TEMPERATURE/HUMIDITY DISPLAY 110 V / 60 HZ .....	46203
TEMP TRACKER- TEMPERATURE/HUMIDITY DISPLAY 230 V / 50-60 HZ .....	46203H
GILL MULTI-PLATE RADIATION SHIELD .....	41002P
RELATIVE HUMIDITY/TEMPERATURE PROBE- 4-20 mA OUTPUT .....	41372LC
TEMPERATURE PROBE- RTD OUTPUT- 4-20 mA OUTPUT (for temperature only).....	41342LC
SENSOR CABLE- 2 PAIR SHIELDED, 22 AWG .....	18723
RACK MOUNTING PANEL- 19" RACK .....	06280



**R. M. YOUNG COMPANY**  
2801 Aero-Park Drive  
Traverse City, Michigan 49686 U.S.A.  
TEL: (616) 946-3980 FAX: (616) 946-4772  
E-mail: met.sales@youngusa.com