

*Reliable Rainfall
Measurement*



Model 52202

Tipping Bucket Rain Gauge

The YOUNG Tipping Bucket Rain Gauge meets the specifications of the World Meteorological Organization (WMO).

The design uses a proven tipping bucket mechanism for simple and effective rainfall measurement. The bucket geometry and material are specially selected for maximum water release, thereby reducing contamination and errors.

Catchment area of 200 cm² and measurement resolution of 0.1 mm meet the recommendations of the WMO. Extensive use of molded thermo-



plastic components ensures maximum performance and value. Leveling screws and bullseye level are built-in for easy and precise adjustment in the field. Measured precipitation is discharged through a collection tube for verification of total rainfall. Model 52202 is heated for operation in cold temperatures. An unheated version, 52203, is available for use in moderate climates.



Specifications

Size:	18 cm dia. x 30 cm high, (39 cm high with mounting base)
Catchment Area:	200 cm ²
Resolution:	0.1 mm per tip
Accuracy:	2% up to 25 mm/hr 3% up to 50 mm/hr
Output:	Magnetic reed switch (N.O.), rating 24VAC/DC 500mA
Operating Temperature:	-20°C to +50°C (heated)
Power:	18 Watts for heater only
Mounting:	Clamp for 1" (1.34" dia.) iron pipe or 3 bolts on 160mm dia. circle
Other:	Leveling adjustment, thermostatic control for heater, intake screen

Ordering Information

MODEL

TIPPING BUCKET RAIN GAUGE (HEATED)	52202
TIPPING BUCKET RAIN GAUGE (UNHEATED)	52203



R. M. YOUNG COMPANY
2801 Aero Park Drive
Traverse City, Michigan 49686 U.S.A.
TEL: (231) 946-3980 FAX: (231) 946-4772
E-mail: met.sales@youngusa.com
Web Site: www.youngusa.com